

formparts

folded glassfibre reinforced
concrete panels for facades

Beton lebt.



RIEDER



Unitised facades made of concrete

It's through the 'industrial manufacture' concept that fibreC glassfibre reinforced concrete panels can be formed into 3D elements whilst maintaining a thickness of only 13 mm. The elements with a monolithic appearance provide architectural concrete's high flexibility and a whole range of design possibilities.

The curved elements are cut-to-measure as an individual piece; they are available as a L-cross-section or U-cross-section respectively, as round arch and also in special shapes. The shaped parts can be combined with the large-format concrete skin facade panels. At a length of up to 4.5 metres, they can take up one whole storey of a home in a single construction element.



LEFT


citizenM Hotel, Tower of London
Sheppard Robson Architects

CENTER

Florentinum Business Office Prague
Cigler Merani Architects


RIGHT

Life Sciences Building, University of Vilnius
UAB Architecture Linija



To secure non-visible fastening, an intelligent system with integrated fastening anchors was developed. Weather-proof pre-assembly in the factory guarantees a high standard of quality and rapid assembly on-site. The elements are simply hung into place and finely-adjusted into position.

Despite their enormous length, and depending on geometry and static factors, formparts can be installed with only two fastening points per element. Thanks to their low weight and the high range of their span, less sub-construction material is needed. As a result, formparts offer an economical solution for the whole building envelope.



Technical data

Forms

L-formpart / U-formpart / round arch / special formpart
 Processing width max. 1300 mm
 Length up to 4500 mm depending on geometry

Colours

12 colours, through-coloured
 Surface: FE ferro (sandblasted)


Product characteristics

Building material class A1 (according to DIN 4102), non-combustible
 Dead load / mass per unit area 26 - 31.5 kg/m² (depending on colour)

Fixing

Rivets, screws, undercut anchor, special solutions

More colours, surfaces and forms are available on request.



Rieder's facade specialists and the company's established network offer support for architects and planners in all project stages, from the early planning phase right through to the implementation. R2R - 'Rendering to Realisation' – is the term characterising this integrative approach at Rieder; it is directed at development of a holistic solution for the envelope of buildings and includes optional service, such as the elaboration of the design, facade optimisation, static calculations, fastening-methods, mock-ups and prototyping, sub-constructions used on elements, pre-assemblies and logistics concepts.



another  **Plastica** product

Plastica Plaat B.V. | Industrieweg 92 | 5145 PW Waalwijk
 Tel. +31(0)416 67 24 00 | info@plastica.nl | www.plastica.nl