

## **DECLARATION OF PERFORMANCE** 1922-CPR-0751/16PP202015031



| 1. Product type Unique identification code of the product type   | Facapal   |  |
|--|---|--|
| <b>2. Type,</b> batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)              | Facapal (lot number see label & marking on product)   |  |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  | Use on walls or ceiling.  |  |
| <b>4. Name,</b> registered trade name or registered trade mark and contact adress of the manufacturer as required under Article 11(5)                        | Plastica Plaat B.V<br>Industrieweg 92<br>5145 PW Waalwijk   |  |
| <b>5. Contact</b> address of the authorised representative whose mandate covers the tasks specified in Article 12(2)   | Not relevant (see 4)  |  |
| <b>6. System</b> or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: AVCP Sysytem: | System 1  |  |
| 7. Notified body In case of the declaration of performance concerning a construction product covered by a harmonised standard (EN 438-7 :2005)               | Notified factory production control certification body NB 1922 performed the initial inspection of the manufacturing plant, factory production control and the continuous surveil- lance, assessment and evaluation of factory production control and issued the certificate of constancy of the factory production control |  |



## **DECLARATION OF PERFORMANCE** 1922-CPR-0751/16PP202015031



## 8. Declared performance:

| Essential characteristics               | Performance                | Harmonised technical specification |
|---|----------------------------|------------------------------------|
| Reaction to Fire                        | Euroclass B-s1, d0         |                                    |
| Fire Resistance                         | NPD                        |                                    |
| Resistance to Fixings                   | < 2000 N                   |                                    |
| Direct Airborne Sound Insulation        | NPD                        |                                    |
| Flexural Strenghth                      | ≥ 90 Mpa                   |                                    |
| Flexural Modulus                        | ≥ 9000 Mpa                 |                                    |
| Thermal Resistance / Conductivity       | NPD                        | EN 438-7:2005                      |
| Release Formaldehyde                    | E1                         |                                    |
| Sound Absorption                        | NPD                        |                                    |
| Thermal Shock Resistance                | PASS                       |                                    |
| Durability Immersion in Boiling Water   | PASS                       |                                    |
| Durability Resistance to Wet Conditions | PASS                       |                                    |
| Density                                 | $\geq 1350 \text{ kg/m}^3$ |                                    |

The performance of the product identified in points 1 and 2 is in confirmity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Waalwijk, The Netherlands, 09.03.2023 (Place and date)

Marc Snoeren

CE0