



Colorstone® exa

DECLARATION OF PERFORMANCE

001CPR01072023



| | |
|--|---|
| 1. Product type Unique identification code of the product type | Colorstone Exa |
| 2. Type , batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) | Extruded Ceramic Clinker Tile |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | For use as facade cladding for internal and external ventilated facade systems. |
| 4. Name , registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) | Paneltex B.V. Industrieweg 92 5145 PW Waalwijk Tel. +31 (0) 416 672 400 E-mail: info@plastica.nl Website: www.plastica.nl |
| 5. Contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) | Not relevant (see 4.) |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: AVCP System: | System 4 |
| 7. Notified body In case of the declaration of performance concerning a construction product covered by a harmonised standard (NEN-EN 14411) | Not relevant |



Colorstone[®] exa

DECLARATION OF PERFORMANCE



8. Declared performance:

| Essential characteristics | Performance | Harmonised technical specification |
|-------------------------------------|---|------------------------------------|
| Reaction to fire | Brandklasse A1 | NEN -EN 13501-1 |
| Fire resistance | - | |
| Waterabsorption | ≤ 0,5% | NEN-EN 14411 |
| Resistance to fixings | Use aluminium AW 6063 or RVS A4-A2 | |
| Direct airborne sound insulation | - | |
| Breaking strength (Thickness ≥ 7,5) | ≥ 3000 N | |
| Bond strength | NPD | |
| Shock resistance | Pass | |
| Dangerous substance: lead cadmium | NPD | |
| Slip Properties | NPD | |
| Thermal shock resistance | Passed | |
| Durability internal use | Passed | |
| Durability external use | Passed | |
| Density | 31.6 kg/m ² (1580 kg/m ³ ± 30kg/m ³) | |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Waalwijk, The Netherlands, 26.01.2023
.....
(Place and date)

.....
Marc Snoeren
CEO