



DECLARATION OF PERFORMANCE

34A202415302



| | |
|--|--|
| 1. Product type Unique identification code of the product type | Alucopal aluminium composite panel various colours consisting of two coated aluminium sheets that are bonded to both sides of a LDPE core. |
| 2. Type , batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) | Alucopal (lot number see label on product) |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | Alucopal panels can be used in buildings as wall and ceiling cladding for outdoor and indoor applications. |
| 4. Name , registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) | Alucopal B.V. Industrieweg 92 5145 PW Waalwijk |
| 5. Contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) | Not relevant (see 4) |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: | System 3 |
| 7. Notified body In case of the declaration of performance concerning a construction product covered by Technical Assessment. | Technical Aproval ITB has been issued by instytut Techniki Budowlanej (ITB), Poland with number KOT2019/1129 on the date 30 december 2019. |

DECLARATION OF PERFORMANCE
34A202415302



8. Declared performance:

| Essential Characteristics | Performance | Harmonised Technical Specification |
|---------------------------|---------------------------|------------------------------------|
| Panel thickness | 4 mm (\pm 0,2 mm) | |
| Panel width | 1250 - 1500 mm (-0/+2 mm) | |
| Panel Length | Max. 6000 mm (-0/+4 mm) | |
| Aluminium skin thickness | 0,50 mm (\pm 0,02 mm) | |
| Core thickness | 3 mm | |
| Peeling resistance | > 12 N/mm | |
| Aluminium Alloy/ Temper | EN AW 3xxx or 5005 H44 | |
| Unit weight | 5,5 kg/m ² | |
| Fire grade | D-s2-d0 | NEN-EN 13501-1 |
| Bending strenght | > 110 N/mm ² | |
| Modulus of Elasticity | > 14000 N/mm ² | |
| Coating type | PVDF | |
| Coating thickness | min. 22 μ | |
| Pencil Hardness | > HB | |
| Salt spray resistance | 500 hours, no change | |
| Humidity resistance | 1000 hours, no change | |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



.....
 Waalwijk, The Netherlands, 29.01.2024
 (Place and date)

.....
 Marc Snoeren
 CEO