



DECLARATION OF PERFORMANCE

34A202415387FRA2



1. Product type Unique identification code of the product type	Alucopal aluminium composite panel various colours consisting of two coated aluminium sheets that are bonded to both sides of a mineral core.
2. Type , batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)	Alucopal FR-A2 (lot number see label on product)
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Alucopal panels can be used in buildings as wall and ceiling cladding for outdoor and indoor applications with high fire resistance requirements.
4. Name , registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5)	Alucopal B.V. Industrieweg 92 5145 PW Waalwijk
5. Contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	Not relevant (see 4)
6. System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 1
7. Notified body In case of the declaration of performance concerning a construction product covered by Technical Assessment	Technical Approval ITB has been issued by instytut Techniki Budowlanej (ITB), Poland with number KOT2019/1129 on the date 30 december 2019.

DECLARATION OF PERFORMANCE
34A202415387FRA2



8. Declared performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Panel thickness	4 mm (\pm 0,2 mm)	NEN-EN 13501-1
Panel width	1250 - 1500 mm (-0/+2 mm)	
Panel Length	Max. 6000 mm (-0/+4 mm)	
Nominal weight per unit area	8,2 kg/m ²	
Aluminium skin thickness	0,50 mm (\pm 0,02 mm)	
Core thickness	3 mm	
Peeling resistance	> 4 N/mm	
Aluminium Alloy/ Temper	EN AW 3XXX or 5005 H44	
Release of formaldehyde	A2 - s1-d0	
Bending strenght	> 90 N/mm ²	
Modulus of Elasticity	> 12000 N/mm ²	
Coating type	PVDF	
Coating thickness	minimum 22 μ	
Pencil Hardness	> HB	
Salt spray resistance	500 hours, no change	
Humidity resistance	1000 hours, no change	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

.....
 Waalwijk, The Netherlands, 03.04.2024
 (Place and date)



.....
 Marc Snoeren
 CEO