

DECLARATION OF PERFORMANCE
30PT202309361L



<p>1. Product type Unique identification code of the product type</p>	<p>Façade cladding: Sawn, planed or profiled with or without tongue and groove.</p>
<p>2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)</p>	<p>Façade cladding, Picea abies (PCAB), external wall and ceilings (lot number see label on product) zweeds rabat 10/22 x 144 mm (various lengths) Channel Siding 20 x 144 mm (various lengths) Board 20 x 144 mm (various lengths) Dimensional tolerance, after wood preservative against biologic attack and after drying, +/- 4 mm</p>
<p>3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:</p>	<p>Finishing of walls and ceilings for external wall applications</p>
<p>4. Name, registered trade name or registered trade mark and contact adress of the manufacturer as required under Article 11(5)</p>	<p>Paneltex B.V. Industrieweg 92 5145 PW Waalwijk Tel. +31 (0) 416 672 400 E-mail: info@plastica.nl Website: www.plastica.nl</p>
<p>5. Contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)</p>	<p>NVT (Zie 4.)</p>
<p>6. System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:</p>	<p>System 4</p>
<p>7. Notified body In case of the declaration of performance concerning a construction product covered by a harmonised standard (NEN-EN 14915:2013 + A2:2020)</p>	<p>NVT</p>

**DECLARATION OF PERFORMANCE
30PT202309361L**



8. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	D-S2-d0	CWFT volgens NEN-EN 14915:2013 + A2:2020 art. 5.1 tabel 1
Water vapour resistance (μ)	60 (vlgs tabel 2)	NEN-EN 14915:2013 + A2:2020 art. 5.6
Resistance to fixings	use stainless steel / pre drilling recommended	NEN-EN 14915:2013 + A2:2020 art. 5.6
Flexural strength	NPD	
Flexural modulus	NPD	
Density	460kg/m ³ bij 12% rv	NEN-EN 14915:2013 + A2:2020 tabel 1
Thermal conductivity (λ)	0,11 W/mk (vlgs tabel 4)	NEN-EN 14915:2013 + A2:2020 art. 5.6
Release of formaldehyde	E1	NEN-EN 13986:2004 + A1:2015
Sound absorption	0,10 (250-500 Hz); 0,30 (1000-2000 Hz) (vlgs tabel 3)	NEN-EN 14915:2013 + A2:2020 art. 5.5 tabel 3
Durability against biologic attack(natural durability, EN 350-1	schimmels 3-4 Insecten: NPD Termieten: NPD Paalwormen: NPD	NEN-EN 350-1:2016
Wood sustainable against fungi	use classes: 2 (EN599-2) retention class: 2 (EN 351-1) Penetration class: 1 mm (EN 351-1)	NEN-EN 599-2 NEN-EN 351-1 NEN-EN 351-1

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Waalwijk, The Netherlands, 03.04.2024
(Place and date)

Marc Snoeren
CEO