



DECLARATION OF PERFORMANCE

06PPC201315000



1. Product type Unique identification code of the product type	Plastica Compact type CGF
2. Type , batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)	Plastica Compact (lot number see label on product)
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Compact laminate for use on internal and external walls and ceilings
4. Name , registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5)	Plastica Plaat B.V. Industrieweg 92 5145 PW Waalwijk
5. Contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	Not relevant (see 4)
6. System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 1
7. Notified body In case of the declaration of performance concerning a construction product covered by a harmonised standard (EN 438-7)	Notified factory production control certification body NB 1085 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of the factory production control.



DECLARATION OF PERFORMANCE

06PPC201315000



8. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Euroclass B-s2, d0 B-s1, d0 for 6-20 mm when installed with max. 15 mm rear ventilation according to classification report MA39-VFA2019-1215	EN 438-7:2005
Fire resistance	NPD	
Water vapour permeability	NPD	
Resistance to fixings	> 2000 N	
Direct airborne sound insulation	NPD	
Flexural strength	≥ 80 MPa	
Flexural modulus	≥ 9000 MPa	
Thermal resistance	NPD	
Release of formaldehyde	E1	
Sound absorption	NPD	
Thermal shock resistance	bestanden / pass	
Durability immersion in boiling water	bestanden / pass	
Durability resistance to wet conditions	bestanden / pass	
Density	≥ 1350 kg/m ³	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Waalwijk, The Netherlands, 11.03.2026

 (Place and date)

.....
 Marc Snoeren
 CEO